

*Reverse Osmosis  
MODEL: Wall Mount  
Gallons per Day: 1,800 to 5,600*

**STANDARD FEATURES:**

- ✓ Powder-coated steel frame
- ✓ Stainless steel multi-stage pump
- ✓ Thin film composite membrane
- ✓ Stainless steel membrane vessel
- ✓ High-pressure nylon tubing
- ✓ Liquid-filled high pressure gauge
- ✓ Liquid-tight wire shrouding
- ✓ Feed water inlet solenoid valve
- ✓ Adjstbl. waste & recycle needle valves
- ✓ Product & waste flow meters
- ✓ 5 micron 10"x4.5" sediment pre-filter
- ✓ Inlet and outlet pre-filter gauges
- ✓ High-pressure brass comp. fittings
- ✓ 110v or 220v-60hz electrical supply
- ✓ Up to 60% feed flow recovery rate

**ELECTRICAL CONTROLS :**

- ✓ NEMA 4 fiberglass enclosure
  - ✓ Off/On switch
  - ✓ Dual level float switches
  - ✓ Low pressure switch
  - ✓ Low pressure bypass delay
  - ✓ Fused control circuit
  - ✓ 24 volt level control circuit
  - ✓ Time delay start
  - ✓ 30 amp motor contactor
- Lights: power, running, low pressure, tank full



**OPTIONS:**

- Automatic hourly flush
- Tank pressure switch (product)
- Pre-treat lock-out with light
- High pressure cut-off w/auto restart and manual override
- TDS digital monitor, panel mounted
- Hour meter
- Recycle flow meter
- 50 hz electrical requirement

**FEED WATER PARAMETERS:** ♦Temperature 85° F maximum ♦Pressure 40 - 80 psi maximum ♦TDS 2000 ppm maximum. If higher, consult factory ♦Iron tolerance 0.5 ppm maximum ♦Hydrogen sulfide must be removed ♦Silica tolerance can not be higher than 125 ppm in the concentrate stream. Antiscalant should be considered for any levels over 75 ppm. ♦Turbidity should be removed ♦Hardness must be removed. **OPERATING PARAMETERS:** ♦Operating pressure 200 psi maximum ♦Water recovery up to 60% and is field adjusted by customer. It is not recommended that the recovery be set higher than 50%. Only under certain conditions can the recovery be set higher. ♦pH range 3 - 11 ♦Flow rates are determined by the membrane mfgr's. testing criteria of 1500 ppm NaCl solution, 77°F water temperature, 225 psi at 10-15% recovery. Typical membrane salt rejection is 95—99%. \*Actual flow rates may vary depending on the pre-treatment used, water conditions, feed water temperature and applied pressure, etc.

**\*Increase GPD at low cost, ask about "shf" membrane**

MODEL	*GPD	MEMBRANE	MOTOR	PIPING			DIMENSIONS
				inlet	waste	prod	
WM 140	1,800 - 2,000	4" x 40" 1ea.	1.5 HP	3/4"	1/2"	1/2"	28" x 15" x 52"H 150 lbs.
WM 240	3,600 - 4,000	4" x 40" 2ea.	2 HP	3/4"	1/2"	1/2"	28" x 15" x 52"H 175 lbs.
WM 340	4,800 - 5,600	4" x 40" 3ea.	2 HP	3/4"	1/2"	1/2"	32" x 15" x 52"H 200 lbs.

Manufactured by:



Phone: 951-940-4300 Fax: 951-346-3904  
Toll-free: 800-477-6464  
E-Mail: [info@rosystemsinternational.com](mailto:info@rosystemsinternational.com)  
[www.rosystemsinternational.com](http://www.rosystemsinternational.com)

Rev: 10-07

